

Max-Seal

THERMOPLASTIC FLOOR SEAL

Product # 032

DESCRIPTION

MAX-SEAL is a high solids seal specially formulated for compatibility with ultra high speed floor coatings. A metal interlock system incorporating state-of-the-art thermal technology, **MAX-SEAL** provides the durable base necessary for ultra high speed buffing. **MAX-SEAL** high solids content builds up a finish base faster than conventional seals, creates a sound foundation for long term protection and flexibility. Non-yellowing, **MAX-SEAL** lets the original beauty of flooring shine through.

USAGE

Designed for use on many different types of floors: vinyl, vinyl asbestos, marble, terrazzo and smooth concrete.

DIRECTIONS

Completely strip old floor finish or wax. Rinse with 2 or 3 clear water rinses. Allow to dry thoroughly. Apply two thin coats of **MAX-SEAL**. Let each coat dry thoroughly. FOR MAXIMUM RESULTS one or more coats should be applied. Allow drying time between coats.

SAFETY INFORMATION

CAUTIONS: May cause eye irritation.

In case of eye contact, flush with plenty of water for at least 15 minutes. Remove contact lenses if applicable. If irritation persists call a physician.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.