

# Heavy Duty Wax & Floor Finish STRIPPER Non-Ammoniated

# STRIP-X HP

**Product # 115**

## DESCRIPTION

Strip-X HP is the most effective labor saving stripper ever developed. Virtually eliminates the need for floor machines, pads, and rinsing. It will solubilize aged and built-up finishes and waxes almost instantly.

The ultimate Floor Stripper is designed to remove floor finish, water-based coatings and sealers from heavily burnished floors.

May be used as a no-scrub floor stripper or with a conventional floor machine and pad depending on the condition of the floor. Can be sprayed on cove moldings to soften and remove accumulations of old finishes and wax.

Removes water-based concrete sealers from resilient tile, Terrazzo, Flagstone, Vinyl (VCT), Ceramic Tile, Asphalt Tile (test first) Rubber (test first) Linoleum, Sealed Wood and Concrete floors.

## FEATURES AND BENEFITS

\* **QUICKLY** penetrates multiple layers of floor finish

\* **FAST ACTING** saves time and labor

\* **FAST** floor stripping action

\* **HIGH ACTIVE** formulation effective on heavy build up

## USAGE

Recommended for commercial, institutional, educational, industrial and household use. Great for commercial stores, public buildings, hospitals and other places with heavy personnel traffic. Use on properly sealed hard floor surfaces, resilient tile, Terrazzo, Flagstone, Vinyl (VCT), Ceramic Tile, Asphalt Tile (test first) Rubber (test first) Linoleum, Sealed Wood and Concrete floors.

## DIRECTIONS

### USE ONLY AS DIRECTED.

The desired concentration will depend on the build-up and age of the polish film. As a starting point dilute with warm water as follows:

On average, 1 gallon of Strip-X HP floor stripper diluted at 1:4 will coverage approximately 500 square feet.

FOR AVERAGE BUILD-UPS: Dilute 1 to 4 with water.

FOR MODERATE BUILD-UPS: Dilute 1 to 3 with water.

FOR HEAVY AGED BUILD-UPS: Dilute 1 to 2 with water.

FOR USE WITH A FLOOR MACHINE: Dilute 1 to 8-16 parts water. Mop a generous solution onto the floor to be stripped. Allow solution to stand about 5 minutes keeping the floor wet at all times. If mop stripping - agitate with the mop. If using an automatic scrubber or rotary floor machine, no mop agitation is required. Pick-up the solution with a wet vacuum, automatic scrubber or clean mop. Rinse with fresh water and allow floor to dry thoroughly prior to applying any sealer or finish.

## PRODUCT SPECIFICATIONS

APPEARANCE	Clear liquid
ODOR	None
SPECIFIC GRAVITY at 77°F	1.1
WATER SOLUBILITY	100%
RINSING	Free rinsing
pH IN CONCENTRATE	12.7
BIODEGRADABLE	Yes
SHELF LIFE	1 Year in unopened container
PACKAGING	55, 35, 15 Gallon drums 5 Gallon pails Cases of 6/1 and 4/1 Gallon jugs

## SAFETY INFORMATION

**CAUTIONS:** Possible skin and eye irritant. Use gloves & safety glasses. Keep container closed when not in use.

All floors are slippery when wet. Wear proper shoes and block off area with "Wet Floor" signs until completely dry.

**KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.**

### FIRST AID

**SKIN:** Wash with plenty of soap and water. **EYES:** Rinse with water for at least 15 minutes. Seek medical attention. **INGESTION:** Do not induce vomiting. Consult a physician immediately.

**Quality**  **Chemical**

1835 N.E. 144th Street, North Miami, Florida 33181  
(305) 944-2837 • (888) 355-5540 • Fax (305) 944-6857  
[www.QualityChemical.com](http://www.QualityChemical.com)